

N1 Series Thermoplastic Emergency Light

Adjustable Square Heads

Features

- Injection molded, high impact, UV-stabilized thermoplastic construction
- Compact, low profile design in white and black finishes
- Universal mounting plate with quick-connect feature reduces installation labor
- Universal mounting pattern knockouts in backplate for J-box mounting
- Fully adjustable glare-free lighting heads
- Dual voltage 120/277 VAC operation
- Maintenance-free 6V sealed lead calcium battery
- Available with HO option for remote loads
- Supplied with 6V, 5.4W incandescent wedge base lamps

Mounting

Suitable for wall or ceiling mounting • Mounting plate includes universal mounting pattern for simple mounting over J-box



Applications

Contemporary design, full adjustability, quick installation and premium options in a stylish and economical package.

Code Compliance

- UL 924
- Damp location rated*
- NFPA 101 Life Safety Code Compliant
- NEC and OSHA Compliant

Ordering Information — Standard Units

Catalog Number	Finish	Output Voltage	Lamp Wattage	Rated Output Watts		
				1 1/2 hrs.	2 hrs.	4 hrs.
N1WH	White	6V	2 x 5.4W	11	-	-
N1BL	Black	6V	2 x 5.4W	11	-	-
N1WHSD (Self-Diagnostic)	White	6V	2 x 5.4W	11	-	-
N1BLSD (Self-Diagnostic)	Black	6V	2 x 5.4W	11	-	-

Ordering Information — High Output Units

Catalog Number	Finish	Output Voltage	Lamp Wattage	Rated Output Watts		
				1 1/2 hrs.	2 hrs.	4 hrs.
N1WHHO	White	6V	2 x 5.4W	16.5	11	-
N1BLHO	Black	6V	2 x 5.4W	16.5	11	-
N1WHHOSD (Self-Diagnostic)	White	6V	2 x 5.4W	16.5	11	-
N1BLHOSD (Self-Diagnostic)	Black	6V	2 x 5.4W	16.5	11	-

For remote heads, see pages 1088 and 1089.

Electrical Data

Lamps Supplied with 6V, 5.4W incandescent wedge base lamps

Input Voltage	Max. Amps	Max. Watts
120	0.04	3.4
277	0.02	4.2

Battery Maintenance-free 6V sealed lead calcium battery • Standard battery will operate fixture for a minimum of 90 minutes in the event of a power outage • High Output version will operate a total of 16.5 watts for a minimum of 90 minutes • Lead calcium battery warranted for one full year

Battery Type	Battery Voltage	Temperature Range ¹
Lead Calcium (Std.)	6V, 4.5Ah	40°F-95°F
Lead Calcium (HO)	6V, 7Ah	40°F-95°F

¹To obtain rated life and capacity

Accessories

Catalog Number	Description
NVS3	Polycarbonate Vandal Shield - Small Bubble
NWG1	Wire Guard - Small

Accessories are ordered separately. To order, specify catalog number. Refer to Accessories section pages 1104-1106 for additional information.

Dimensions

